

Domestic

3 Strand Twisted Prodac Combination Rope

Color: White with Black Tracer

Diameter	Circumference	Part Number	Breaking	Weight Per	Length
			Strength In LBS	Reel/Coil In LBS	
1/4"	3/4"	800-1500	1,454	8.7	600'
5/16"	1"	800-1600	2,198	13.7	600'
3/8"	1-1/8"	800-1800	2,919	19.7	600'
1/2"	1-1/2"	800-2000	4,682	33.8	600'
5/8"	2"	800-2200	7,997	51.9	600'
5/8"	2"	800-2210	7,997	103.8	1,200'
3/4"	2-1/4"	800-2400	10,791	73.7	600'
1"	3"	800-2600	16,490	121	600'
1-1/4"	3-3/4"	800-2800	24,899	185.3	600'
1-1/2"	4-1/2"	800-3000	35,677	260.9	600'
1-3/4"	5-1/2"	800-3200	50,715	349.7	600'
2"	6"	800-3600	56,152	456.8	600'
2-1/4"	7"	800-3900	69,146	569.6	600'
2-1/2"	7-1/2"	800-0	86,776	699.4	600'
2-5/8"	8"	800-4100	92,729	779.3	600'

Prodac



Extralene



Poly-Plus



3 Strand Twisted Combination Rope

600'

Lengths

Diameter	Circumference	Part Number	Breaking	Weight Per	Type
			Strength In LBS	Reel/Coil In LBS	
1-5/8"	5"	800-3005	42,150	339.9	Poly-Plus
1-5/8"	5"	800-3006	42,150	330	Extralene
2"	6"	800-3500	81,865	486	Starline
2"	6"	800-3700	61,400	486	Extralene
2-1/4"	7"	800-3800	101,915	606	Starline
2-5/8"	8"	800-4200	137,105	816	Starline

Starline

