



Fiber Core



IWRC

6 x 19 Classification Galvanized Wire Rope

According to Federal Specification RR-W-410E. Meets the performance requirements of API-9A, and A.S.T.M. A1023/1023M Wire Rop for General Purposes, as applicable. Preformed, right regular lay.

IMPROVED PLOW STEEL Fiber Core IPS				EXTRA IMPROVED IWRC EIPS			
Diameter Inches	Approx. Weight Per Foot Pounds	Nominal Breaking Strength Net Tons	Part Number	Approx. Weight Per Foot Pounds	Nominal Breaking Strength Net Tons	Part Number	Diameter Inches
1/4"	0.105	2.74	210-0	0.116	3.4	210-0	1/4"
*5/16"	0.164	4.69	210-545	0.18	5.27	210-150	**5/16"
3/8"	0.236	6.1	210-550	0.26	7.55	210-155	3/8"
7/16"	0.32	8.27	210-0	0.35	10.2	210-165	7/16"
1/2"	0.42	10.7	210-555	0.46	13.3	210-170	1/2"
9/16"	0.53	13.5	210-0	0.59	16.8	210-180	9/16"
5/8"	0.66	16.7	210-560	0.72	20.6	210-185	5/8"
3/4"	0.95	23.8	210-565	1.04	29.4	210-195	3/4"
7/8"	1.29	32.2	210-570	1.42	39.8	210-200	7/8"
1"	1.68	41.8	210-575	1.85	51.7	210-205	1"
1-1/8"	2.13	2.13	210-580	2.34	65	210-210	1-1/8"
1-1/4"	2.53	2.63	210-0	2.89	79.9	210-215	1-1/4"
1-3/8"				3.5	96	210-220	1-3/8"
1-1/2"				4.16	114	210-225	1-1/2"
1-5/8"				4.88	132	210-0	1-5/8"
1-3/4"				5.67	153	210-0	1-3/4"
2"				7.39	198	210-0	2"

*EIPS Fiber
Core

**6x19 "S"