



7 x 7 Galvanized Steel Cable

| Size | Part Number | Approx. Weight Per 1,000/ft In LBS | Breaking Strength In LBS |
|-------|-------------|---|--------------------------------|
| 1/16" | 300-1100 | 7.5 | 480 |
| 3/32" | 300-1200 | 16 | 920 |
| 1/8" | 300-1300 | 28 | 1,700 |
| 5/32" | 300-1400 | 43 | 2,600 |
| 3/16" | 300-1500 | 62 | 3,700 |
| 1/4" | 300-1600 | 106 | 6,100 |



7 x 19 Galvanized Steel Cable

| Size | Part Number | Approx. Weight Per 1,000/ft In LBS | Breaking Strength In LBS |
|-------|-------------|---|--------------------------------|
| 3/32" | 300-100 | 17.4 | 1,000 |
| 1/8" | 300-300 | 29 | 2,000 |
| 5/32" | 300-200 | 45 | 2,800 |
| 3/16" | 300-400 | 65 | 4,200 |
| 7/32" | 300-600 | 86 | 5,600 |
| 1/4" | 300-700 | 110 | 7,000 |
| 5/16" | 300-800 | 173 | 9,800 |
| 3/8" | 300-900 | 243 | 14,400 |

Not intended for aircraft use but designed for industrial and marine applications according to

Federal Specification RR-W-410E and A.S.T.M. A 1023/A 1023M, as applicable.