



## 7 x 7 - 7 x 19 Coated Galvanized Cable

Cable Diameter	Coated To	Part Number	Coating	Color	Approx. Weight Per 1,000 Ft. In LBS	Breaking Strength In LBS	Construction
1/16"	3/32"	300-1900	Vinyl	Clear	9.3	480	7 x 7
1/16"	1/8"	300-2010	Vinyl	Clear	11.8	480	7 x 7
3/32"	1/8"	300-0	Vinyl	Clear	18.5	920	7 x 7
3/32"	3/16"	300-2200	Vinyl	Clear	25.8	920	7 x 7
1/8"	3/16"	300-2100	Vinyl	Clear	35.2	1,700	7 x 7
1/8"	3/16"	300-2400	Vinyl	Clear	36.2	2,000	7 x 19
1/8"	3/16"	300-2500	Vinyl	Orange	36.2	2,000	7 x 19
1/8"	3/16"	300-2600	Nylon	Black	36.2	2,000	7 x 19
3/16"	1/4"	300-2700	Vinyl	Clear	77.5	4,200	7 x 19
3/16"	1/4"	300-2710	Nylon	Black	77.5	4,200	7 x 19
1/4"	5/16"	300-2800	Vinyl	Clear	123	7,000	7 x 19
5/16"	3/8"	300-2900	Vinyl	Red	197	9,800	7 x 19
5/16"	3/8"	300-2910	Vinyl	Clear	197	9,800	7 x 19
3/8"	7/16"	300-3000	Vinyl	Clear	270	14,400	7 x 19
3/8"	7/16"	300-3010	Vinyl	Black	270	14,400	7 x 19

Not intended for aircraft use but designed for industrial and marine applications. When using wire rope clips with coated cable, match clip size to uncoated cable diameter (3/16" coated to 1/4" takes a 3/16" clip.) Strip coating off the cable where the clips will be positioned for full holding power. Uncoated cable according to Federal Specification RR-W-410E. Uncoated galvanized cable is in accordance with A.S.T.M. A1023/1023M as applicable.