


Oblong Alloy Master Links

Part Number	Diameter	Working Load Limit In LBS	W	L	Weight Each In LBS
600-16600	1/2"	4,920	2-3/4"	4-3/4"	0.97
600-16605	5/8"	6,600	3.00"	5-1/2"	1.45
600-16700	3/4"	10,320	3-3/4"	6-1/4"	2.64
600-16800	1"	24,380	4-5/8"	7-1/2"	5.57
1200-05200	1-1/4"	35,160	5-1/8"	9.00"	10.38
600-17100	1-1/2"	47,880	5-1/4"	10-1/2"	16.5
600-17300	1-3/4"	62,520	6.00"	12.00"	24.8
600-17400	2"	97,680	7.00"	14.00"	37.6

All above links are proof tested to twice the working load limit.



Pear Shaped Carbon Sling Link

Part Number	Diameter	Working Load Limit In LBS	L x W1 x W2	Weight Each In LBS
600-16510	3/8"	1,800	2.25" x 1.50" x 0.75"	0.25
600-16520	1/2"	2,900	3.00" x 2.00" x 1.00"	0.58
600-0	3/4"	6,000	4.50" x 2.75" x 1.38"	1.92
600-16705	7/8"	8,300	5.25" x 3.50" x 1.75"	3.03
600-16810	1"	10,800	6.00" x 3.75" x 1.88"	4.58
600-16900	1-1/4"	16,750	7.75" x 5.00" x 2.50"	8.96

All above links are proof load tested

