



Closed Spelter Sockets

Part Number	Size	A	B	C	D	E	F	G	H	Weight Each In LBS
1200-23310	5/16"-3/8"	4.88"	0.94"	0.63"	0.50"	2.25"	2.00"	1.69"	0.69"	1.1
1200-23311	7/16"-1/2"	5.44"	1.13"	0.69"	0.56"	2.50"	2.25"	2.00"	0.88"	1.5
1200-0	9/16"-5/8"	6.31"	1.38"	0.81"	0.69"	3.00"	2.50"	2.63"	1.00"	3
1200-23400	3/4"	7.56"	1.63"	1.06"	0.81"	3.50"	3.00"	3.00"	1.25"	4.5
1200-0	7/8"	8.75"	1.88"	1.25"	0.94"	4.00"	3.50"	3.63"	1.50"	7
1200-23600	1"	9.88"	2.25"	1.38"	1.13"	4.50"	4.00"	4.13"	1.75"	11
1200-22100	1-1/8"	11.00"	2.50"	1.50"	1.25"	5.00"	4.50"	4.50"	2.00"	16
1200-22200	1-1/4"	12.13"	2.75"	1.63"	1.50"	5.50"	5.00"	5.00"	2.25"	22
1200-22500	1-3/8"	12.13"	2.75"	1.63"	1.50"	5.50"	5.00"	5.00"	2.25"	22
1200-22600	1-1/2"	13.94"	3.13"	1.94"	1.63"	6.00"	6.00"	5.38"	2.50"	28
1200-0	1-5/8"	15.38"	3.25"	2.13"	1.75"	6.50"	6.75"	5.75"	2.75"	36
1200-22700	1-3/4"-1-7/8"	17.25"	3.53"	2.19"	2.00"	7.50"	7.56"	6.75"	3.00"	58
1200-23000	2"-2-1/8"	19.50"	3.78"	2.44"	2.25"	8.50"	8.56"	7.63"	3.25"	80
1200-23200	2-1/4"-2-3/8"	21.38"	4.28"	2.88"	2.50"	9.00"	9.50"	8.50"	3.63"	105
1200-23300	2-1/2"-2-5/8"	23.50"	5.50"	3.13"	2.88"	9.75"	10.63"	9.50"	4.00"	140

Hot Galvanized. Forged sockets through 1-1/2". Alloy cast steel 1-5/8" and larger

Meets performance requirements of Federal Specification RR-S-550D Amendment 1