

# Eye Hoist Hooks

\*Working Load Limit applies only when the load is applied to the center of the saddle of the hook

Size (WLL)*		Part Numbers				Dimensions In Inches											Approx. Weight
Carbon	Alloy	Carbon Import	Alloy Import	Carbon Domestic	Alloy Domestic	A	B	C	D	E	F	G	H	J	K	In Lbs	
Tons	Tons																
3/4	1	600-3700		1200-12900		1.5	0.75	0.38	0.88	0.63	0.94	2.88	0.75	4.38	3.25	0.6	
1	1-1/2	600-4200			1200-13000	1.75	0.88	0.44	1	0.69	1.06	3.13	0.81	4.88	3.63	0.82	
1-1/2	2	600-4500			1200-13100	2	1.13	0.44	1.19	0.81	1.06	3.5	1	5.5	4.13	1.44	
2	3	600-4700	600-5100		1200-13400	2.38	1.25	0.59	1.38	0.94	1.22	3.94	1.19	6.31	4.56	1.94	
3	5	600-4900	600-5300	1200-13300	1200-13705	3	1.56	0.69	1.63	1.19	1.5	5	1.5	7.94	5.75	3.94	
5	7	600-5200	600-5500	1200-13700	1200-13760	3.81	2	0.88	2.06	1.5	1.88	6.25	1.75	10	7.38	7.75	
7-1/2	11	1200-6600	600-5700	1200-13800	1200-14000	4.69	2.44	1.13	2.63	1.63	2.25	7.56	2.25	12.4	9.06	15.4	
10	15		600-5900	1200-13900	1200-14100	5.37	2.84	1.26	2.94	2.19	2.51	8.3	2.59	13.9	10.07	22.2	
15	22	600-6000			1200-14200	6.64	3.5	1.58	3.5	2.69	3.3	10.3	3	17.1	12.5	37.6	

