



Galvanized Bolt Type Anchor Shackles

Size A	Part Number	Working Load Limit	Bolt Diameter B	Approx. Weight Each In LBS	C	D	E	F
3/8"	500-24100	1 ton	7/16"	0.33	1.44"	0.66"	0.91"	1.03"
1/2"	500-24200	2 ton	5/8"	0.9	1.88"	0.81"	1.31"	1.25"
5/8"	500-24300	3-1/4 ton	3/4"	1.6	2.44"	1.06"	1.56"	1.69"
3/4"	500-24500	4-3/4 ton	7/8"	2.8	2.88"	1.19"	1.88"	1.94"
7/8"	500-25600	6-1/2 ton	1"	4.2	3.38"	1.44"	2.13"	2.19"
1"	500-24700	8-1/2 ton	1-1/8"	6.4	3.81"	1.69"	2.38"	2.63"
1-1/8"	500-24800	9-1/2 ton	1-1/4"	8.3	4.25"	1.75"	2.63"	2.88"
1-1/4"	500-24900	12 ton	1-3/8"	11.7	4.69"	2"	3"	3.13"
1-1/2"	500-25000	17 ton	1-5/8"	19.7	5.69"	2.31"	3.50"	3.75"
1-3/4"	500-25100	25 ton	2"	32.6	7.06"	2.88"	4.25"	4.88"
2"	500-25200	35 ton	2-1/4"	48.3	7.75"	3.31"	4.88"	5.44"
2-1/4"	500-0	45 ton	2-1/2"	67	9.25"	3.63"	5.25"	5.50"
2-1/2"	500-25300	55 ton	2-3/4"	94	10.75"	4.13"	5.88"	7.25"

Meets the performance requirements of Federal Specification RR-C-271, Type IV A, Class 3, Grade A, Amendment 1