



Drop Forged Galvanized Wire Rope Clips

Size	Domestic Part Numbers	Imported Part Numbers	Dimensions In Inches							Min Clips Req'd.	Torque In Foot LBS*
			A	B	C	D	E	F	G		
1/8"	1200-0	500-12900	0.19	0.75	0.44	0.44	0.38	0.81	0.94	2	4.5
3/16"	1200-23800	500-13000	0.25	0.94	0.56	0.56	0.5	0.94	1.19	2	7.5
1/4"	1200-23900	500-13100	0.31	1.06	0.56	0.75	0.63	1.19	1.5	2	15
5/16"	1200-24000	500-13200	0.38	1.44	0.75	0.88	0.75	1.31	1.69	2	30
3/8"	1200-24100	500-13300	0.44	1.5	0.75	1	0.88	1.56	1.94	2	45
7/16"	1200-24120	500-13400	0.5	1.88	1	1.19	1	1.81	2.31	3	65
1/2"	1200-24200	500-13500	0.5	1.88	1	1.19	1.06	1.81	2.31	3	65
9/16"	1200-0	500-13600	0.56	2.38	1.25	1.31	1.13	2.06	2.5	3	95
5/8"	1200-24300	500-13700	0.56	2.38	1.25	1.31	1.25	2.06	2.5	3	95
3/4"	1200-24400	500-13800	0.63	2.75	1.38	1.5	1.38	2.31	2.75	4	130
7/8"	1200-24500	500-13900	0.75	3.19	1.44	1.81	1.69	2.63	3.31	4	225
1"	1200-24600	500-14000	0.75	3.63	1.75	1.88	1.75	2.63	3.47	5	225
1-1/8"	1200-24800	500-14100	0.75	4	2	2	1.88	2.81	3.56	6	225
1-1/4"	1200-24700	500-14200	0.88	4.38	2.25	2.31	2.06	3.25	4.06	7	360
1-3/8"	1200-24850	500-14300	0.88	4.63	2.31	2.38	2.25	3.44	4.25	7	360
1-1/2"	1200-24900	500-14400	0.88	4.94	2.38	2.63	2.5	3.5	4.38	8	360
1-5/8"	1200-0	500-14500	1	5.31	2.62	2.75	2.66	3.61	4.75	8	430
1-3/4"	1200-24905	500-14600	1.13	5.88	2.75	3.06	2.88	3.75	5.25	8	590
2"	1200-25000	500-14700	1.25	6.5	3	3.31	3.38	4.44	5.81	8	750
2-1/4"	1200-0	500-14800	1.25	7.13	3.31	3.88	3.81	4.5	6.31	8	750
2-1/2"	1200-0	500-0	1.25	7.75	3.38	4.13	4.25	4.5	6.44	9	750

* Based on clean, lubricated threads. The table above shows the minimum torque required to reach maximum holding power of wire rope clips.