



Galvanized Screw Pin Anchor Shackles

| Size A | Part Number | Working Load Limit | Pin Diameter B | Approx. Weight Each In LBS | C | D | E | F |
|-----------|----------------|--------------------------|----------------------|-------------------------------------|-------|-------|-------|-------|
| 3/16" | 500-20900 | 1/3 ton | 1/4" | 0.05 | 0.88" | 0.38" | 0.56" | 0.63" |
| 1/4" | 500-21000 | 1/2 ton | 5/16" | 0.13 | 1.06" | 0.47" | 0.66" | 0.75" |
| 5/16" | 500-21100 | 3/4 ton | 3/8" | 0.21 | 1.25" | 0.53" | 0.81" | 0.84" |
| 3/8" | 500-21200 | 1 ton | 7/16" | 0.33 | 1.44" | 0.63" | 0.97" | 1" |
| 7/16" | 500-21300 | 1-1/2 ton | 1/2" | 0.47 | 1.69" | 0.75" | 1.06" | 1.13" |
| 1/2" | 500-21400 | 2 ton | 5/8" | 0.78 | 1.88" | 0.81" | 1.31" | 1.25" |
| 5/8" | 500-21600 | 3-1/4 ton | 3/4" | 1.44 | 2.44" | 1.06" | 1.56" | 1.69" |
| 3/4" | 500-21700 | 4-3/4 ton | 7/8" | 2.3 | 2.88" | 1.19" | 1.88" | 1.94" |
| 7/8" | 500-21800 | 6-1/2 ton | 1" | 3.5 | 3.38" | 1.44" | 2.13" | 2.19" |
| 1" | 500-21900 | 8-1/2 ton | 1-1/8" | 5 | 3.81" | 1.69" | 2.38" | 2.63" |
| 1-1/8" | 500-22000 | 9-1/2 ton | 1-1/4" | 7 | 4.25" | 1.75" | 2.63" | 2.88" |
| 1-1/4" | 500-22100 | 12 ton | 1-3/8" | 9.5 | 4.69" | 2" | 3" | 3.13" |
| 1-3/8" | 500-22200 | 13-1/2 ton | 1-1/2" | 13 | 5.31" | 2.13" | 3.25" | 3.50" |
| 1-1/2" | 500-22300 | 17 ton | 1-5/8" | 16.5 | 5.69" | 2.31" | 3.50" | 3.75" |
| 1-3/4" | 500-22400 | 25 ton | 2" | 29 | 7.06" | 2.88" | 4.25" | 4.88" |
| 2" | 500-22500 | 35 ton | 2-1/4" | 43 | 7.75" | 3.31" | 4.88" | 5.44" |

Meets the performance requirements of Federal Specification RR-C-271, Type IV A,
Class 2, Grade A, Amendment 1