



Galvanized Screw Pin Chain Shackles

Size A	Part Number	Working Load Limit In Tons	Pin Diameter B	Approx. Weight Each In LBS	C	D	E
1/4"	500-22800	1/2 ton	5/16"	0.09	0.88"	0.50"	0.63"
5/16"	500-22900	3/4 ton	3/8"	0.17	1"	0.53"	0.78"
3/8"	500-23000	1 ton	7/16"	0.32	1.28"	0.69"	0.97"
1/2"	500-23100	2 ton	5/8"	0.8	1.72"	0.84"	1.28"
5/8"	500-23200	3-1/4 ton	3/4"	1.3	2.03"	1.06"	1.50"
3/4"	500-23300	4-3/4 ton	7/8"	2.2	2.41"	1.25"	1.81"
7/8"	500-23400	6-1/2 ton	1"	3.2	2.91"	1.72"	2.13"
1"	500-23500	8-1/2 ton	1-1/8"	5.1	3.25"	1.75"	2.38"
1-1/8"	500-23600	9-1/2 ton	1-1/4"	6.5	3.56"	1.81"	2.63"
1-1/4"	500-23700	12 ton	1-3/8"	9	3.97"	2"	2.91"
1-3/8"	500-23800	13-1/2 ton	1-1/2"	12.2	4.56"	2.19"	3.25"
1-1/2"	500-23900	17 ton	1-5/8"	17	5"	2.34"	3.50"

Meets the performance requirements of Federal Specification RR-C-271, Type IV B,

Class 2, Grade A, Amendment 1.