



Open Spelter Sockets

Part Number	Size	A	B	C	D	E	F	G	H	Weight Each In LBS
1200-22000	7/16"-1/2"	5.56"	1.00"	1.00"	0.56"	2.50"	2.00"	1.88"	0.50"	2.3
1200-23500	9/16"-5/8"	6.75"	1.25"	1.19"	0.69"	3.00"	2.50"	2.25"	0.56"	3.8
1200-22104	3/4"	7.94"	1.50"	1.38"	0.81"	3.50"	3.00"	2.63"	0.63"	6
1200-22102	7/8"	9.25"	1.75"	1.63"	0.94"	4.00"	3.50"	3.13"	0.75"	10
1200-23605	1"	10.56"	2.00"	2.00"	1.13"	4.50"	4.00"	3.75"	0.88"	15.5
1200-22099	1-1/8"	11.81"	2.25"	2.25"	1.25"	5.00"	4.50"	4.13"	1.00"	22
1200-22106	1-1/4"-1-3/8"	13.19"	2.50"	2.50"	1.50"	5.50"	5.00"	4.75"	1.13"	32
1200-0	1-1/2"	15.13"	3.00"	2.75"	1.63"	6.00"	6.00"	5.38"	1.19"	46
1200-22107	1-5/8"	16.25"	3.00"	3.00"	1.75"	6.50"	6.50"	5.75"	1.31"	55
1200-22105	1-3/4"-1-7/8"	18.25"	3.50"	3.50"	2.00"	7.00"	7.00"	6.50"	1.56"	85
1200-23606	2"-2-1/8"	21.50"	4.00"	3.75"	2.25"	9.00"	9.00"	7.00"	1.81"	125
1200-0	2-1/4"-2-3/8"	23.50"	4.50"	4.25"	2.50"	10.00"	10.00"	7.75"	2.13"	165
1200-0	2-1/2"-2-5/8"	25.50"	5.00"	4.75"	2.88"	10.75"	10.75"	8.50"	2.38"	252

Hot Galvanized. Forged sockets through 1-1/2". Alloy cast steel 1-5/8" and larger
 Meets performance requirements of Federal Specification RR-S-550D
 Amendment 1