



## Open Swage Socket

C-1035 Steel - Also available in 304 Stainless Steel: 3/8" - 1-1/4"

Part Number	Rope											Weight	After
	Size	A	B	D	E	F	H	L	M	O	Y	Each In LBS	Swage Min-Max
1200-0	3/8"	0.770"	0.406"	0.812"	1-3/4"	6-1/4"	3-3/16"	5-5/16"	13/32"	13/16"	1-5/8"	1.2	.678-.710
1200-0	7/16"	0.982"	0.484"	1.00"	2"	7-13/16"	4-1/4"	6-11/16"	1/2"	1"	2"	2.45	.865-.910
1200-21893	1/2"	0.982"	0.547"	1.00"	2"	7-13/16"	4-1/4"	6-11/16"	1/2"	1"	2"	2.4	.865-.911
1200-0	9/16"	1.257"	0.609"	1.19"	2-1/4"	9-9/16"	5-5/16"	8-1/8"	5/8"	1-1/4"	2-1/2"	4.8	1.115-1.160
1200-23501	5/8"	1.257"	0.672"	1.19"	2-1/4"	9-9/16"	5-5/16"	8-1/8"	5/8"	1-1/4"	2-1/2"	4.5	1.115-1.161
1200-0	3/4"	1.545"	0.796"	1.380"	2-3/4"	11-11/16"	6-3/8"	10"	3/4"	1-1/2"	3"	7.8	1.365-1.420
1200-21898	7/8"	1.700"	0.938"	1.630"	3-1/4"	13-5/8"	7-7/16"	11-5/8"	15/16"	1-3/4"	3-3/8"	11.8	1.490-1.550
1200-0	1"	1.975"	1.062"	2.00"	3-3/4"	15-5/8"	8-1/2"	13-3/8"	1-1/32"	2"	4"	17.8	1.740-1.800
1200-21906	1-1/8"	2.245"	1.188"	2.250"	4-1/4"	17-1/2"	9-9/16"	15"	1-3/16"	2-1/4"	4-1/2"	28.9	1.990-2.050
1200-21905	1-1/4"	2.525"	1.328"	2.250"	4-3/4"	19-7/16"	10-5/8"	16-1/2"	1-3/16"	2-1/2"	5"	36.2	2.240-2.300
1200-21908	1-3/8"	2.800"	1.453"	2.250"	5-1/4"	21-1/4"	11-11/16"	18-1/8"	1-5/16"	2-1/2"	5-1/4"	47.7	2.490-2.560
1200-21910	1-1/2"	3.075"	1.578"	2.750"	5-3/4"	23-1/4"	12-3/4"	19-3/4"	1-7/16"	3"	5-3/4"	64.4	2.740-2.810
1200-0	1-3/4"	3.385"	1.859"	3.500"	6-3/4"	27-1/8"	14-7/8"	23"	1-11/16"	3-1/2"	7"	93.4	2.990-3.060
1200-0	2"	3.935"	2.109"	3.750"	8"	31-7/16"	17"	26-3/4"	1-13/16"	4"	8"	148	3.490-3.560
1200-0	2-1/4"	4.450"	2.360"	4.250"	6-3/4"	32-7/8"	19-1/8"	27-3/4"	2-9/16"	4-1/2"	8-3/4"	173	3.950-4.020
1200-0	2-1/2"	4.930"	2.657"	4.250"	6-3/4"	34-5/8"	19-5/8"	29-1/2"	2-9/16"	4-1/2"	8-3/4"	233	4.350-4.420

Sockets properly applied have an efficiency rating of 100%. This rating is based on the catalog strength of the wire rope.