



## T-Type Underground Pulling Grip

Part Number	Cable Diameter	Approx. Breaking Strength In LBS	E	M
<b>Short</b>				
#033041082	.50"-.62"	4,500	8"	21"
#033041083	.63"-.74"	5,600	8"	24"
#033041084	.75"-.99"	6,800	9"	24"
#033041085	1.00"-1.49"	9,600	9"	24"
#033041086	1.50"-1.99"	16,400	11"	24"
#033041087	2.00"-2.49"	18,500	12"	24"
#033041088	2.50"-2.99"	24,500	12"	24"
#033041089	3.00"-3.49"	24,500	14"	24"
#033041090	3.50"-3.99"	31,000	14"	26"
<b>Standard</b>				
#033041091	.75"-.99"	6,800	9"	36"
#033041092	1.00"-1.49"	9,600	9"	36"
#033041093	1.50"-1.99"	16,400	11"	36"
#033041094	2.00"-2.49"	18,500	12"	36"
#033041095	2.50"-2.99"	24,500	12"	36"
#033041096	3.00"-3.49"	24,500	14"	36"
#033041097	3.50"-3.99"	31,000	14"	40"

Kellems Flexible T-Type Pulling Grips are made of high strength galvanized steel strand . They feature double weave mesh for positive holding power in medium to heavy pulling jobs. The grip eye will easily attach to a swivel.