



Zinc Plated Malleable Wire Rope Clips

Size	Part Numbers	Dimensions In Inches							Min Clips Req'd.	Torque In Foot LBS*
		A	B	C	D	E	F	G		
1/16"	500-19400	0.15	0.65	0.45	0.38	0.38	0.45	0.69	3	2
1/8"	500-19500	0.18	0.81	0.5	0.5	0.5	0.56	0.94	3	3
3/16"	500-19600	0.25	0.94	0.56	0.56	0.56	0.63	1.06	3	4.4
1/4"	500-19700	0.31	1.19	0.75	0.75	0.69	0.75	1.31	3	15
5/16"	500-19800	0.31	1.31	0.84	0.75	0.75	0.75	1.44	3	15
3/8"	500-19900	0.38	1.63	1	0.88	0.84	0.88	1.63	3	30
7/16"	500-20000	0.44	2	1.19	1.06	1	1.06	1.88	4	40
1/2"	500-20100	0.44	2	1.19	1.06	1	1.06	1.88	4	45
9/16"	500-20200	0.5	2.31	1.38	1.25	1.25	1.28	2.09	4	50
5/8"	500-20300	0.5	2.31	1.38	1.25	1.25	1.28	2.09	4	75
3/4"	500-20400	0.56	2.56	1.56	1.31	1.44	1.56	2.38	5	75
7/8"	500-20500	0.63	3.06	1.81	1.63	1.81	1.81	2.88	5	130
1"	500-20600	0.63	3.44	2	1.88	2.06	2	3	6	130
1-1/8"	500-20700	0.75	4	2.75	2	2.19	2.06	3.38	7	200

* Based on clean, lubricated threads. The table above shows the minimum torque required to reach maximum holding power of wire rope clips.

NEVER use cast malleable wire rope clips for lifting or suspending ANY load.

Use only for non-critical, light duty applications with small applied loads.